

CASH® Captive Bolt Stunning Tool Performance Information

To Whom It May Concern

The table below provides the key parameters relating to the **CASH®** Magnum Auto humane stunning tool manufactured by Frontmatec Accles & Shelvoke.

This information is issued to help business operators comply with the EU Council Regulation 1099/2009.

Frontmatec Accles & Shelvoke have developed the parameters after years of experience of manufacture and development of the listed tool.

It is advised that these figures may only be used when quoted with the associated notes.

Frontmatec Accles & Shelvoke will not accept responsibility for the provenance of these figures if used out of context.

On behalf of Frontmatec Accles&Shelvoke Ltd



Joe Holland

Vice President of Bolt Stunning

Product: CASH® Magnum Auto
Calibre: .22
Product code: 5652R and 5652AS with stop fire feature

Tool	Cartridge grains (nominal)	Cartridge (colour)	Bolt diameter (mm)	Average bolt velocity* (m/s)	Exit length** minimum (mm)	Energy generated (J)
CASH® Magnum Auto .22	1.25	Pink	11.43	42.73	65	213
CASH® Magnum Auto .22	2	Purple	11.43	48.21	65	271
CASH® Magnum Auto .22	3	Green	11.43	53.41	65	332
CASH® Magnum Auto .22	4	Red	11.43	59.12	65	407
CASH® Magnum Auto .22	4.5	Black	11.43	59.87	65	418

*When measured in air over a distance of 47 mm, 15 mm from the muzzle of the tool

**When fired in air

The figures quoted are accurate within +/-15%, when using a stunner that is in good condition and maintained in accordance with this instruction manual.

Contact

Accles & Shelvoke Ltd
 Unit 5A, Maybrook Road, Maybrook Business Park
 Minworth Sutton Coldfield
 Birmingham, West Midlands
 UK B76 1 AL

Phone: +44 121 313 3564
 Fax: +44 121 313 0282
 E-mail: birmingham@frontmatec.com
accles-shelvoke.com
frontmatec.com