

## CASH® Captive Bolt Stunning Tool Performance Information

### To Whom It May Concern

The table below provides the key parameters relating to the **CASH®** Special humane stunning tool manufactured by Frontmatec Accles & Shelvoke.


This information is issued to help business operators comply with the EU Council Regulation 1099/2009.

Frontmatec Accles & Shelvoke have developed the parameters after years of experience of manufacture and development of the listed tool.

It is advised that these figures may only be used when quoted with the associated notes.

Frontmatec Accles & Shelvoke will not accept responsibility for the provenance of these figures if used out of context.

On behalf of Frontmatec Accles&Shelvoke Ltd



Joe Holland

Vice President of Bolt Stunning

**Product: CASH® Special**

**Calibre: .22**

**Product code: 4100R**

Tool	Cartridge grains (nominal)	Cartridge (colour)	Bolt diameter (mm)	Average bolt velocity* (m/s)	Exit length** minimum (mm)	Energy generated (J)
CASH® Special .22	1.25	Pink	11.43	42.3	65	189
CASH® Special .22	2	Purple	11.43	47.5	65	238
CASH® Special .22	3	Green	11.43	52.5	65	291

\*When measured in air over a distance of 47 mm, 15 mm from the muzzle of the tool

\*\*When fired in air

The figures quoted are accurate within +/-15%, when using a stunner that is in good condition and maintained in accordance with this instruction manual.

## Contact

Accles & Shelvoke Ltd  
Unit 5A, Maybrook Road, Maybrook Business Park  
Minworth Sutton Coldfield  
Birmingham, West Midlands  
UK B76 1 AL

Phone: +44 121 313 3564  
Fax: +44 121 313 0282  
E-mail: [birmingham@frontmatec.com](mailto:birmingham@frontmatec.com)  
[accles-shelvoke.com](http://accles-shelvoke.com)  
[frontmatec.com](http://frontmatec.com)